

# **Model 387RB-2**

**WITH** 

**CENTRA-LUBE®** 

SEMI-AUTOMATIC LUBRICATION SYSTEM


LARGE VERTICAL AXIS ROTARY HOOKS AND BOBBINS

REVERSE FEED

SAFETY CLUTCH









HEAVY DUTY
CYLINDER ARM
TWO NEEDLE
DROP FEED, NEEDLE FEED
WALKING FOOT
ALTERNATING PRESSER FEET
LOCKSTITCH MACHINE





### **Model 387RB-2**

#### **APPLICATIONS**

- For sewing light to heavy-weight fabrics, leather, vinyl, upholstery, synthetics, canvas and various coated and laminated materials
- Designed for stitching tubular and curved work.
- Suitable for sewing such products as caps, cushions, boots, shoes, auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, orthopedic appliances, slippers, filters, etc.













#### **FEATURES**

- Two needle mechanism readily makes two parallel lines of stitches
- Large vertical axis rotary hooks and bobbins assure longer operation between bobbin changes
- Compound feed, walking foot mechanism assures even feeding of several plies or of slippery materials Centra-Lube® semi-automatic lubrication system
- Reverse feed
- Safety clutch prevents the hook from being damaged
- Simple adjustment permits the raising and lowering of the center foot which allows for sewing of different thicknesses of material
- Various needle gauges available

## SPECIFICATIONS

Speed M	/lax. (S.P.M.)*	2500*	Hook	13719
— Speed, IV	idx. (5.1 .ivi.)	2300	TIOOK	10.10
Clearance	e Under Foot	<sup>11</sup> / <sub>32</sub> " (8.5mm)	Bed Size	3 <sup>7</sup> / <sub>32</sub> " dia. x 13" (82mmØ x 330mm)
Needle B	ar Stroke	1 <sup>5</sup> / <sub>16</sub> " (33.2mm)	Work Space	10" (254 mm)
Stitch Le	ngth, Max.	@4 s.p.i. (6.2 mm)	Stitch Type	301
Bobbin	Metal	15041	Needle	135 x 17
Dobbili	Pre-wound	S	Standard Needle Spacings: 1/8", 1/4", 3/8", 1/2"	

<sup>\*</sup> Speed depends on materials, thread and operation.